

# Advanced HVAC Design for Better Performance



Understanding HVAC Design Software Programs to Optimize Comfort and Efficiency (And Catch Mistakes Before It's Too Late)

This presentation is the intellectual property of Carbon Neutral Group Consulting LLC, and duplication or distribution without licensing or written legal consent is prohibited, and protected by intellectual property law.

## HVAC Design Goals Ductwork that Delivers

The goal of HVAC designers & contractors: Is to...

- Choose proper equipment size/capacity,
- Reduce "total static-pressure",
- Reduce "total effective length" With...
- Less restrictive filters and A/C coils,
- Smooth transitions and better air-flow, *To...*
- Deliver the right amount of heating and cooling to each unique room on all levels of the home, for year-round comfort and optimized efficiency.



## Better HVAC Design Reduce Static-Pressure & Effective Length

#### Advantages of Computer Designed HVAC Systems:

- Enables HVAC system to maintain even temperatures throughout the whole building with just one blower/fan and one thermostat,
- Solves the problems of: over-heated upper floors, rooms out of sync with the rest of the house, and cold basements, just to name a few,
- Increases the useful life of the HVAC equipment, with fewer repairs and system failures.



A low staticpressure system delivers: ample airflow w/less noise, to the entire home, and improves efficiency too!

## Building Code Requirements Tools for Best Performance

### Manual J: Block Loads and Losses

 Calculates the total heating or cooling capacity needed to maintain desired interior temperatures on the hottest or coldest days,

### Manual D: Ductwork Design

 Calculates the exact "room-by-room" heating and cooling needed to offset summer heat gains & winter heat losses, and sizes ducts accordingly,

## Manual S: HVAC Equipment Sizing

• Calculates best size of air-conditioner and furnace for whole house comfort & efficiency.



## HVAC Design Basics Tools for Best Performance

### Manual J: Total Loads and Losses

- Calculates the total heating and cooling capacity needed to maintain desired indoor temperature on the hottest or coldest days,
- Does not calculate heating/cooling needed for individual rooms or floors in the building,
- Shows energy losses/gains by each building component: ceiling, walls, windows, foundation, infiltration, duct work, humidification, and ventilation.



This home needs 48k BTU of heating when it's 4° outside, and 25k BTU of Cooling when it's 91° outside.

## HVAC Design Basics Manual D for Ductwork

## Manual D Duct Design:

Delivers required heating and cooling (temps and air-flow) room by room with precise duct layout and dimensions.

Detailed Inputs include:

- Glass: orientation, type/specs, square feet, overhangs (eaves),
- Details for: ceilings, wall type, floors over garage, w/materials and R-values,
- Foundation details for: crawlspace, below grade walls, slabs, w/R-values.



## HVAC Design Basics Manual S for Right-Sizing

### Manual S: Equipment Sizing

- Calculates best size of air-conditioner and furnace for whole house comfort & efficiency,
- Use <u>total building loads/losses</u>, AND required *air-flow and temps* to pick the right sized equip.

#### **Technical Specs:**

- Air-flow target for air-conditioning = 450 CFM's per Ton (12,000 BTU's) in dry, hot climates,
- Air-flow target **forced-air heating = 150 CFM's** per 10,000 BTU's of rated heating capacity.



Many AC systems are still over-sized.

## Better HVAC Design Manual D Ductwork Challenges

Example: Three-level home with 12 separate spaces/rooms, and only one fan and thermostat:

How do we ensure ample heating and cooling air-flow throughout the building?



#### Design Challenges:

- Static Pressure,
- Total Effective Length,
- Friction Rate,
- Need Chases for Risers,





## Better HVAC Design Reduce Static Pressure and Effective Length

The actual length these two sections of ductwork is the same, but the difference in "effective-length" is huge.

The longer the total effective-length of a ductwork system, the less likely it will be able to deliver the needed air-flow throughout the building, especially the longest ducts. BRANCH LOSS COEFFICIENT - APPX. 1.20 (HEIGHT/WIDTH = 1.0)



LACK OF TURNING VANES CAUSES EXCESSIVE TURBULENCE IN FITTING: RESULTS IN VERY HIGH PRESSURE DROP

Effective Length of this 90° bend = <u>60 - 120 feet</u>!



AIRFLOW, GREATLY REDUCING TURBULENCE; RESULTS IN VERY LOW PRESSURE DROP

Effective Length of this 90° bend = <u>only 10 feet!</u>

## Better HVAC Design Manual D Ductwork Concepts

#### **Key Elements of Duct Design:**

- Set maximum external static • pressure at factory spec >
- Enter accurate pressure • losses for components >
- Subtract static-pressure • losses for HVAC components = available static-pressure >
- Total effective length of • entire system/longest run >
- Friction-rate must stay • above 0.06, or weak air-flow

Static Pressure for Entire House

	Heating (in H2O)
External static pressure	<0.50>
Pressure losses	
Coil	0.25
Heat exchanger	0
Supply diffusers	0.03
Return grilles	0.03
Filter	0.15
Humidifier	0
Balancing damper	0
Other device	0
Available static pressure	0.04

<b>Cooling</b> (in H2O)	Sector Constraints		Supply (ft)	
	Measured leng	th of run-out	33	
0.25	Measured leng	th of trunk	12	
0	Equivalent leng	th of fittings	335	•••
0.03			-	-
0.03	Total length		379	
0.15	Total effective	length		
0				
0	Friction Rate	Heating	С	ool
0		(in/100ft)	(ir	1/10
	Supply	[0.007] < 0.06	5 [0	.00
0.04	Return	[0.007] < 0.06	5 [0	.00

FR = Friction Rate ASP = Available Static Pressure TEL = Total Effective Length

$$FR = \frac{ASP}{TEL} \times 100$$

Return

Cooling

(in/100ft)

[0.007] < 0.06

[0.007] < 0.06

(ft)

150 •••

159

538

## Better HVAC Design Manual D Ductwork Challenges

#### Accuracy is Essential:

- Don't set the static pressure above equipment's rated max,
- Use accurate static-pressure drop across AC evap coil,
- Use accurate static-pressure drop across filter,
- Using inaccurate data (at *right*) will result in systems that don't perform in the real world.

Static Pressure for Entire House Cooling Heating Supply Return (in H2O) (in H2O) (ft) (ft) External static pressure <0.60> Measured length of run-out Pressure losses 33 9 Measured length of trunk 12 Coil 0.10 0.10 1 Heat exchanger Equivalent length of fittings 335 ••• 150 ••• 0 0 0.03 Supply diffusers 0.03 0.03 0.03 **Return grilles** Total length 379 159 0.10 0.10 Total effective length 538 Filter Humidifier 0 0 Friction Rate **Balancing damper** 0 Heating Cooling 0 Other device (in/100ft) (in/100ft) 0 0 Supply [0.063] OK [0.063] OK Available static pressure 0.34 0.34 [0.063] OK [0.063] OK Return

If available static-pressure, total effective-length, and friction-rate are acceptable, the software says "OK", and if not, it says "<0.06" (which is the minimum). In this case, the inputs are not accurate, and the system only works on paper.

## Better HVAC Design New Energy Efficient Fan Motors



"These motors need to breathe"

Standard PSC\* Motor = 45% efficient

DC-brushless ECM\* = 85% efficient

But restrictive ductwork with high-static pressure negates the advantage:

Ideal =	0.25 i.w.c.
Max =	0.50 i.w.c.
Typical =	0.80 i.w.c.

\*PSC = permanent split capacitor, \*ECM = electronically commutated motor i.w.c. = inches water column of pressure



Evaluation of Retrofit Variable-Speed Furnace Fan Motors -Consortium for Advanced Residential Buildings January 2014 <u>https://www.nrel.gov/docs/fy14osti/60760.pdf</u>

Apply better design for low static-pressure to improve air-flow to the farthest ends of the HVAC system:



RESULTS IN VERY LOW PRESSURE DROP

Dramatic improvement in performance for an additional cost of only \$200 - \$500 on \$10,000 to \$20,000 systems:



The Advantages of the "Sled-pack":

- Over-sized jumbo 4" media filter with lowpressure drop,
- Radius elbow in return plenum,
- Air-box directly under blower fan/motor assembly.



Filter Area = 2.0 square feet for each 400 cfm of air flow! (wide-pleated filters have lots of surface area)

#### **Outdated Design = Poor Performance:**

- The typical "T" plenum-to-supply trunk-line junction has an effective length of **120 ft!**
- Resulting in elevated static-pressure, weak air-flow to longest effective runs, and uneven temps throughout the building.

At right: Duct fittings chart with effective-length, from Manual D duct-design software > Group 1. Supply Air Fitting at the Air Handling Equipment



#### **Better Design = Better Performance:**

- "Tapered" transitions reduce effective length of furnace plenum to supply trunk line junction to only **10 feet!**
- Resulting in moving more air with less effort, and more uniform temps throughout the building.

Duct fittings chart with effective-length, from Manual D duct-design software > Group 1. Supply Air Fitting at the Air Handling Equipment

Picture	ID	Eq.Len.	Fitting Description	-
12	1C	35	90 deg. rect. take-off	
	1D	10	90 deg. rect. tapered take-off	_
	1E	10	90 deg. rect. tapered take-off	
hunder	1F1	120	Rect. header - no transition, H/W = 0.5	-
1.F	1F2	85	Rect. header - no transition, H/W = 1.0	
	1G1	35	Expanding rect. header with transition, H/W = 0.5	-
Sup at A/H	up take-	offs (Re	ducing take-offs 🖌 Sup boots/stacks 🔏 Ret at A/H 🔏 Ret BR 🕯	fittin
		OK	Cancel Clear	

Indoor AC Evaporator Coil Issues: Static Pressure and Air-flow: Typical Pressure Drop = 0.25 - 0.35 iwc High Air-flow Coil = 0.09 - 0.15 iwc Higher Air-flow Coil = only \$100 extra!

#### Notes:

Upsize coil by ½ ton = higher SEER rating, TXV is critical for efficiency, costs \$100.





# Better Supply-side Airflow for Air-Conditioning:

- Upsize indoor AC-coil to improve SEER-rating and cooling capacity,
- Wider AC-coils reduces pressure drop across the evaporator coil,
- Access door allows for inspection and cleaning of clogged AC-coils.



System Service Transition (SST) cost \$115

## Better Duct Design Ductwork "Tinner" Fundamentals

- Limit trunk-lines to 24 ft in length without reductions, or 48 ft total from centrally located unit,
- Lower width-to-height ratios have lower friction losses so make trunks as square as possible (8' standard not always best),
- No take-offs within 24" of trunk end cap,
- Never locate a takeoff in the end cap,
- When the trunk is wider than the plenum, a transition fitting must be used,
- Provide 120% return-air to supply-air ratio for vent and duct dimensions, or more.



## HVAC Design Ductwork Mistakes that Matter

# Never locate a takeoff in the end cap, and no take-offs within two feet of trunk-line end cap:



Five supply branches in last 2ft of trunk line, causing comfort issues in the rest of the home.

## HVAC Design Ductwork Mistakes that Matter

# Four supply-air branches in the last two feet of supply trunk:



# Upstream supply branches receive little air-flow:



## Better HVAC Design Ductwork Mistakes that Matter

# Avoid supply vents in trunk-line, use branch take-offs:



# Mistakes in branches & trunks causes weak, uneven air-flow:



## Better HVAC Design Ductwork Mistakes that Matter

Sags and bends decrease air-flow, flex duct needs stretch & support:



Hard/metal radius elbows should be used for flex-duct as necessary:



A round 14" return-duct compressed to 6" oval:

## Better HVAC Design for Ductwork that Delivers

### HVAC Design and Commissioning:

- Improvements and "Best Practices" are becoming more standardized,
- Higher operational efficiency delivers lower heating/cooling costs, superior climate-control and customer satisfaction.





#### Recommended Diagnostic Testing for Ductwork Airflow & Comfort:

- Total system air-flow,
- Correct static-pressure,
- Amp-draw for fan-motor,
- Duct-leakage is acceptable,
- Room-by-room air flows are correct,
- Attic-based systems are extremely tight, well insulated and installed.



## Better HVAC Design Ductwork that Delivers

To Learn More about Energy Codes or Green Building, please contact: Community Development <u>https://www.larimer.org/building</u> Building: 970-498-7700 or Planning: 970-498-7683



Presentation prepared by: <u>Michael C. Truitt</u> <u>CarbonNeutralGroup.com</u> <u>info@carbonneutralgroup.com</u> 970-204-9931 / 719-850-1921



This presentation is the intellectual property of Carbon Neutral Group Consulting LLC, and duplication or distribution without licensing or without written legal consent is prohibited and protected by intellectual property law.